

## RECON™

### Heavy-Duty Cleaner

#### Product Description

3027-Orange

RECON Heavy Duty Cleaner is a powerful, water soluble, cleaner and degreaser. Due to its chemical potency, this product is extremely effective in the removal of heavy accumulations of grease, oil, fats, carbon, ink, wax, dirt, soot, tar, asphalt, creosote, rust stains and many soils. It contains a fast acting powerful solubilizing agent that dissolves and suspends any soil, allowing it to be wiped or rinsed away completely.

#### Application Information

##### DIRECTIONS

FOR LIGHT DUTY CLEANING: Dilute 2 ounces of concentrate per gallon of water.

FOR MOP CLEANING OR MACHINE SCRUBBING OF FLOOR FINISHES OR MEDIUM DUTY CLEANING: Dilute 3 or 4 ounces of concentrate per gallon of water

FOR HEAVY DUTY INDUSTRIAL CLEANING: Dilute 6 to 8 ounces of concentrate per gallon of water. Apply a liberal amount of solution onto the surface to be cleaned and allow to stand for a few minutes to allow product to penetrate into soil. Brush or scrub surface and pick-up. Rinse thoroughly with clean water.

FOR USE IN AUTOMATIC SCRUBBERS: For daily maintenance of non-industrial floors, dilute 3 to 4 ounces of concentrate (depending on soil conditions) to each gallon of water in the solution tank. For use in heavy industrial applications, dilute 8 to 12 ounces of concentrate (depending on soil conditions) to each gallon of water in the solution tank.

FOR USE IN PRESSURE WASHERS: Adjust spray nozzle to deliver 1 part concentrate to 30-60 parts water depending on soil conditions. Rinse thoroughly with clear water.

These directions are flexible rather than specific. In many cases a more dilute solution can be used, while for extreme conditions a less dilute solution may be used.

This product meets the maximum content requirements for Volatile Organic Compounds (VOCs) as established by State and Federal regulations.

##### CAUTION

WARNING: EYE AND SKIN IRRITANT. Avoid contact with skin, eyes, and clothing. Wear protective rubber gloves when handling. Wear protective eyewear (chemical splash goggles) where potential for mist contact may occur. Use in well ventilated areas. Avoid breathing of vapors or mists. Do not take internally. Harmful if swallowed. Keep out of the reach of children. For professional use only.

##### FIRST AID

EYE CONTACT: Flush with water while holding eyelids open for at least 15 minutes. Call a physician immediately.

SKIN CONTACT: Remove contaminated clothing. Wash thoroughly with water. If irritation persists, call a physician immediately.

INGESTION: Do not induce vomiting. Immediately drink large quantities of water. Contact a physician.

INHALATION: Remove to fresh air. Seek medical attention if symptoms persist.

##### CAUTION!

##### KEEP OUT OF REACH OF CHILDREN.

Do not take internally. Close container after each use.

Keep from freezing.

Store between 40°F (4.5°C) and 90°F (32°C)

24 hour Emergency "CHEM-TEL" -  
800.255.3924

#### Properties

##### Product Specifications

Active Ingredient:	11.5 ± 0.5%
Color:	Orange
Odor:	Mild
Foam:	Moderate
Flash Point:	Non-combustible
pH:	12.0-13.0
Shelf Life:	24 Months Min. (Original Sealed Container)

##### Dilutions

Soot & Carbon Removal:	1:16
Heavy Duty Cleaning:	1:16
Medium Duty Cleaning:	1:32
Steam Cleaning/Pressure Wash:	1:32
General Cleaning:	1:64
Hard Floor Cleaning:	1:64

##### Available Package Sizes

1 gallon containers (4/case)



## Application Information

### For Technical Information call 800.342.3755

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither ICP Construction, Inc., nor its agents shall be responsible for the use or results of use of this product or any injury, loss or damage, direct or consequential. We recommend that the prospective user determine the suitability of this product for each specific project and for the health and safety of personnel working in the area.

*RECON™, the RECON™ Logo and other marks in this literature are trademarks of ICP Construction, Inc.*