



GREEN GLUE PAIL APPLICATOR GUN GUIDE

Green Glue Noiseproofing Compound is available in both 28 ounce tube cartridges and 5 gallon pails. Deciding to use pails or tubes depends on the size and type of soundproofing project. Tubes are perfect for smaller residential projects which are under approximately 800 square feet. Once a project is larger than 4+ cases of tubes, its highly recommended to use Green Glue pails. Green Glue in 5 gallon pails will reduce the cost of material by approximately 30% along with cutting the application time as well. This guide will explain how to properly use the Green Glue Pail Applicator Gun.

Prepare Green Glue Applicator Gun for Use

Screw the nozzle ring off of the front of the gun and place the dispensing cone inside the ring and reattach. Cut the tip of the cone to create a 1/2" opening. Nozzles cut too small will increase loading and dispensing time.



Lubricate Green Glue Applicator Gun

If the plunger is tight when the rod is pulled back, you should lubricate the barrel. Spray lubricant on the inside of the barrel chamber while you have the gun pointing upward to prevent dripping. While pressing the rod recoil button, pull the plunger rod all the way into the full position and then back again.

Load Green Glue Applicator Gun

While holding the gun with one hand, dip the orange cone into the pail of Green Glue. With your other hand pull back on the plunger rod while pressing the rod recoil button with your thumb. Pull the rod as far back as allowed while keeping the cone under the surface of the Green Glue.



BIP TIP:

If the plunger rod is still tight after greasing the plunger, adjust the small screw on the top of the rod recoil button



Dispense Green Glue

Once the Green Glue Applicator is full, the Green Glue can now be dispensed by simply pulling the trigger. Make sure to go around the perimeter of the drywall allowing a 2" space. This prevents Green Glue from seeping through the drywall joints.



Make Random Pattern

Apply 2 dispensers worth of Green Glue to each 4' x 8' sheet of drywall. The pattern can be random however try your best to provide full coverage over the entire sheet.

Fasten 2nd Layer of Drywall

Within 15 minutes of dispensing Green Glue onto the drywall, screw the drywall into the first layer making sure to stagger the joints of both layers. Caulk all wall, floor, and ceiling joints with acoustical caulk



Clean Applicator with Soap & Warm Water

Immediately after use, clean the Green Glue Applicator Gun with soap and warm water. The barrel and plunger can be detached to make cleaning easier.

Green Glue Noiseproofing Compound
 5 Gallon Pails - [Learn More](#)