

Product Data Sheet

X-70 Plus

Product Description

Anabec's X-70 Plus is a microbial barrier product specifically designed for application to unfinished building surfaces, including wood fibers, brick, block and unfinished drywall, among others. The product uses the anti-microbial properties of silver and advanced coatings technology which allows the active ingredients to penetrate a materials surface, allowing the product to work from within the material.



Application of X-70 Plus, results in an extremely durable barrier which can resist mold and mildew growth.

Application Information

X-70 Plus is a second step in the Anabec System of Products. It is applied after cleaning the surface with Advanced Cleaning Solution.

This product is appropriate for use on previously cleaned unfinished building material surfaces such as drywall, plaster, concrete, brick and wood.

The X-70 Plus product can serve as a primer for latex paints on raw building materials

The product can be applied with an airless sprayer. Airless sprayer tip size 0.011 – 0.015.

Available in clear, white or Anabec Blue.

User should check material compatibilities prior to application to hydrocarbon based building materials.

General Characteristics

Ready to Use Surface penetrant Microbial barrier Leaves faint sheen

Properties

Appearance Clear, White. Blue
Odor faint solvent
pH neutral
Density 8.40 lbs/gals
Viscocity (Zahn #2) 13-15 secs
Flash Point not combustible
Calculate VOC 0.335 lbs/gal

Packaging / Use

5 gallons RFU

Do NOT allow to freeze

Shelf Life 1 year
Coverage 800-1000 sq ft / gallon
Dry to touch 2 hours
Dry to recoat 18-24 hours

Stir prior to use

Cleanup with Soap/Water